

11/21/00

BIRCH, STEWART, KOLASCH & BIRCH, LLP

INTELLECTUAL PROPERTY LAW

8110 GATEHOUSE ROAD

SUITE 500 EAST

FALLS CHURCH, VA 22042-1210

USA

(703) 205-8000

FAX (703) 205-8050

(703) 698-8590 (G IV)

e-mail: mailroom@bskb.com

web: http://www.bskb.com

CALIFORNIA OFFICE
COSTA MESA, CALIFORNIA

THOMAS S. AUCHTERLAGE
JAMES T. ELLER, JR.
SCOTT L. LOWE
MARK J. NUEL, PH.D.
D. RICHARD ANDERSON
PAUL C. LEWIS
MARK W. MILSTEAD*
RICHARD J. GALLAGHER
JAYNE M. SAYDAH*
MARYANNE ARMSTRONG, PH.D.
HYUNG N. SOHN
ALAN PEDERSEN-GILES
KECIA J. REYNOLDS

REG. PATENT AGENTS.
FREDERICK R. HANDREN
MAKI HATSUMI
MIKE S. RYU
CRAIG A. McROBBIE
GARTH M. DAHLEN, PH.D.
ROBERT E. GOOZNER, PH.D.
MATTHEW J. LATTIG
TIMOTHY R. WYCKOFF
KRISTI L. RUPERT, PH.D.
LARRY J. HUME
ALBERT K. LEE
HAYR A. SAYADIAN, PH.D.
EVE L. FRANK, PH.D.
MATTHEW T. SHANLEY

TERRELL C. BIRCH
RAYMOND C. STEWART
JOSEPH A. KOLASCH
JAMES M. SLATTERY
BERNARD L. SWEENEY*
MICHAEL K. MUTTER
CHARLES GORENSTEIN
GERALD M. MURPHY, JR.
LEONARD R. SVENSSON
TERRY L. CLARK
ANDREW D. MEIKLE
MARC S. WEINER
JOE MCKINNEY MUNCY
ROBERT J. KENNEY
DONALD J. DALEY
JOHN W. BAILEY
JOHN A. CASTELLANO
GARY D. YACURA

OF COUNSEL
HERBERT M. BIRCH (1905-1996)
ELLIOT A. GOLDBERG*
WILLIAM L. GATES*
EDWARD H. VALANCE
RUPERT J. BRADY (RET)*
F. PRINCE BUTLER
FRED S. WHISENHUNT

*ADMITTED TO A BAR OTHER THAN VA

Date: November 21, 2000

Docket No.: 1920-0115P

Assistant Commissioner for Patents
Box PATENT APPLICATION
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of

Inventor(s): SOKOLOV, Skiff

For: NOISE REDUCTION IN IMAGES

Enclosed are:

X A specification consisting of 24 pages

 sheet(s) of drawings

X An assignment of the invention

X Certified copy of Priority Document(s)

X Executed Declaration X Original Photocopy

X Applicant claims small entity status in accordance with 37 CFR 1.27

 Application Data Sheet in accordance with 37 C.F.R. 1.76

 Preliminary Amendment

X Information Disclosure Statement, PTO-1449 and reference(s)

STATEMENT CLAIMING SMALL ENTITY STATUS
(37 CFR 1.9(f) & 1.27(c)) - SMALL BUSINESS CONCERN

Docket Number: 1920-0115P

Applicant, Patentee, or Identifier: Tom Francke

Application or Patent No.: New

Filed or Issued: November 21, 2000

Title: NOISE REDUCTION IN IMAGES

I hereby state that I am

- ☐ the owner of the small business concern identified below:
☒ an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF SMALL BUSINESS CONCERN XCounter AB

ADDRESS OF SMALL BUSINESS CONCERN Svärdvägen 3B, SE-182 33 Danderyd, Sweden

I hereby state that the above identified small business concern qualifies as a small business concern as defined in 37 CFR Part 121 for purposes of paying reduced fees to the United States Patent and Trademark Office, in that the number of employees of the concern, including those of its affiliates does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time part-time, or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby state that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention described in:

- ☒ the specification filed herewith with title as listed above.
☐ the application identified above.
☐ the patent identified above.

If the rights held by the above identified small business concern are not exclusive, each individual, concern, or organization having rights in the invention must file separate statements as to their status as small entities, and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 CFR 1.9(f) if that person made the invention, or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d), or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern, or organization having any rights in the invention is listed below:

- ☒ no such person, concern, or organization exists.
☐ each such person, concern, or organization is listed below.

Separate statements are required from each named person, concern, or organization having rights to the invention stating their status as small entities. (37 CFR 1.27)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is not longer appropriate. (37 CFR 1.28(b))

NAME OF PERSON SIGNING Tom Francke

TITLE IN ORGANIZATION OF PERSON SIGNING President

ADDRESS OF PERSON SIGNING Hemgårdsvägen 2, SE-191 44 Sollentuna, Sweden

SIGNATURE Tom Francke

DATE 20 Sept 2000



Intyg Certificate

Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.

- (71) Sökande Xcounter AB, Danderyd SE
Applicant (s)
- (21) Patentansökningsnummer 0003608-7
Patent application number
- (86) Ingivningsdatum 2000-10-06
Date of filing

Stockholm, 2000-10-18

För Patent- och registreringsverket
For the Patent- and Registration Office

Anita Södervall
Anita Södervall

Avgift
Fee 170:-

BSKB 103-205 BOX
SOKOLOV, SKIFF
1920- OHSF
1051



FIELD OF INVENTION

5 BACKGROUND

10

15

25

This object is among others attained by methods as claimed in claim 1, 6, or 9, and by a computer program product as claimed in claim 16.

An advantage of the present invention is achieved by utilization of different methods in dependence on information known of noise or image structure, whereby improved noise reduction is achieved in accordance with said information.

5 Further features and advantages of the present invention will be evident from the following description.

DETAILED DESCRIPTION OF EMBODIMENTS

10 In the following description, for purpose of explanation and not limitation, specific details are set forth, such as particular techniques and applications in order to provide a thorough understanding of the present invention. However, it will be apparent to one skilled in the art that the present invention may be practiced in other embodiment that depart from these specific details. In other instances, detailed
15 descriptions of well-known methods and apparatuses are omitted so as not to obscure the description of the present invention with unnecessary details.

The present invention can, if some additional information about noise or image structure, besides the image itself, is
20 given, be used to improve noise reduction and reduce the image-degrading consequence incurred by the noise reduction. Four important examples of such additional information is the knowledge that an image has one or several of the following properties:

25 (a) almost all the area of the true image, i.e. of the noise free image, is covered by many-pixel fragments, wherein the intensity is changing smoothly;

(b) the dispersion or other parameters of noise reduction, such as FWHM (full width at half maximum), are approximately
30 known;

(c) the noise in the image is significantly correlated with the noise in other images (or in different parts of the same image); and

(d) the image is computed (reconstructed) from source data,
5 which are common to source data of other images.

Most images have property (a), though the sizes and shapes of smooth fragments may vary much from image to image.

Property (b) is valid for most noisy images, including X-ray pictures.

10 Properties (c) and (d) are valid for most reconstructed images, including tomographic images and maps of bone density reconstructed from dual-energy X-ray images.

Although the noise in an image may be correlated with the noise in other images or portions thereof for many technical
15 reasons, the most frequent cause of such correlation is the origin of images from the same source data. When several images are computed (reconstructed) from the same data, the same initial noise enters into all the computed images thereby making the noise, obtained by reconstruction,
20 correlated.

The noise in reconstructed images is usually strongly amplified compared to the noise in source data and becomes an imminent problem, which can be solved by the methods of the present invention as will be described below. An important
25 example is the calculation of bone and soft tissue densities from two X-ray images of the same part of body, but made with X-rays of different energies. Since the reconstruction of the densities is based on the small differences between such X-ray images, the reconstructed densities are very sensitive to
30 the noise in these source images and the noises in the

reconstructed images are relatively large and are strongly correlated with each other.

The properties (a), (b), (c), and (d) give new possibilities of noise reduction which were not fully exploited before.

5 Methods of noise reduction will be described which using properties (a), (b), (c), and (d) accomplish deeper noise reduction and diminish the smearing consequence incurred by it. Especially deep noise reduction without any smearing of small details is achievable for the reconstructed images when
10 methods using properties (a), (b), (c), and (d) are combined.

Noise in an image is generally any contamination dirt covering the true-image of the object of interest. The shapes of dirt fragments and the statistical properties of dirt may be quite different. The present invention concerns mainly the
15 noise, which looks as dark and light spots or grains scattered over the whole image and covering it densely. If the image of the same or different object is produced again, e.g. another X-ray image taken of a patient, these spots lie at different places in that image than in the first image.

20 The high-frequency noise in pixel images consists of small spots of the size of one or two pixels. Such noise is often seen in images made by high sensitive films and electronic cameras made in conditions of poor illumination or low X-ray flux, when the number of registered photons over a pixel area
25 is not large.

The pixel value p at some point X in a noisy image can be considered as a sum of a mean value P , which the pixel would have in a true image, without noise, and of fluctuation F , wherein the pixel value p is given by the formula:

30
$$p = P + F.$$

The expression "mean value" is denoted by the symbol M , so that $P = M(p)$, and $M(F) = 0$. The main parameter of such noise, describing its strength, is dispersion D . The dispersion $D(X)$ is defined as a mean value of the squared fluctuation for pixel X , which is given by the formula:

$$D(X) = M(F^2).$$

The quality of an image is usually characterized by the so-called signal-to-noise ratio (S/N), which is actually defined as P^2/D . The noise reduction makes the dispersion D smaller and improves S/N .

The mean value $M(FG)$ of the product of fluctuations F, G of two pixel values $p = P(X) + F$, $g = P(Y) + G$ at different points X, Y (Y may be the point with same coordinates as X but lying in a different image) is called covariance of values p, g . This quantity together with dispersions of p, g makes 2×2 covariance matrix

$$V = \begin{pmatrix} V_{11} & V_{12} \\ V_{21} & V_{22} \end{pmatrix},$$

with elements,

$$V_{11} = M(F^2) = D(X),$$

$$V_{12} = V_{21} = M(FG),$$

$$V_{22} = M(G^2) = D(Y).$$

The strength of the mutual dependence of fluctuations F, G is measured by the correlation coefficient C , which is given by the formula:

$$C = V_{12} / \sqrt{V_{11} V_{22}},$$

which may vary from -1 to 1. The values $C = -1$ and $C = 1$ correspond to complete dependence of fluctuations, so F and G are proportional and by knowing F one may thereby calculate G , and vice versa. The dispersion D of the linear combination

5 $\alpha p + \beta g$ of the pixel values p, g is expressed by the formula:

$$D(\alpha p + \beta g) = \alpha^2 V_{11} + \beta^2 V_{22} + 2\alpha\beta V_{12}.$$

The mean value is most often unknown and is approximately estimated by the average value over some number N of independently obtained values x_i of the same quantity x ,
10 wherein the average value of x is given by the formula:

$$\text{Avr}(x) = \sum x_i w_i / \sum w_i,$$

where positive coefficients w_i are weights. If the weights are equal to one, which is adopted if x_i have same accuracy, the average of x is given by the formula:

15
$$\text{Avr}(x) = \sum x_i / N.$$

For example, the true pixel value $P(X)$ at point X may be estimated as $\text{Avr}(p)$ of values p_i of pixels at points Y_i in some area around X , if there are reasons to think that true values P_i differ little from $P(X)$, or their deviations from
20 $P(X)$ compensate each other. The dispersion $D(X)$ may be estimated as the average of the squared deviations from $\text{Avr}(p)$, which is given by the formula:

$$D(X) \approx \text{Avr}((p - \text{Avr}(p))^2),$$

if there are reasons to think that the noise is of the same
25 strength in the chosen area around X . Similarly, covariance V_{12} may be estimated as:

$$V_{12} \approx \text{Avr}((p - \text{Avr}(p))(g - \text{Avr}(g))).$$

The usual methods of noise reduction replace each pixel of an image by the average value over some area around a pixel. This area together with a table of coefficients, with which the pixel values are summed, is usually called a filter. A simple example of a filter is a square of 9 pixels, the values of which are summed with the same coefficient $1/9$ when the average is calculated. Averaging with such filter diminishes the noise dispersion 9 times, but smears the image making each visible line in it 4 pixels wider and correspondingly decreasing its contrast. The methods described in the present invention achieve greater reduction of noise dispersion at the same smearing consequence, or reduce the smearing consequence for the same noise reduction.

A tomographic reconstruction is the calculation of the density of the object on some planes cutting the object using a plurality of X-ray pictures or NMR (Nuclear Magnetic Resonance) data. It is a complex procedure, reconstructing images with correlated noise.

The reconstruction of the densities of the bone and of the soft tissue is more simple and consists of calculation of two functions $a(p,g)$, $b(p,g)$ giving the densities of the bone and soft tissue as functions of pixel values p, g at point X in two X-ray images obtained with X-rays of different energies. The functions $a(p,g)$, $b(p,g)$ are usually obtained from calibration X-ray exposures of objects with known densities of bone and soft tissue equivalents. Both functions are very sensitive to small differences of pixel values $p - g$, so the calculated densities have larger noise dispersions and worse signal-to-noise ratio than the original X-ray images. The noise in the bone density image is strongly correlated with the noise in the soft tissue density image, where the correlation coefficient C is negative and close to -1 .

A first method of noise reduction using property (a) of the true image (presence of smooth fragments) and property (b) of the noise (known dispersion) will now be described.

The first method reduces noise at each point X of an image by averaging the pixel values over a region R, wherein the averaging region R is dependent on X and is selected as the largest region around X, which includes only pairs of pixels Y, Z symmetrically placed with respect to X and having the half sums $(p(Y) + p(Z))/2$ of values deviating from each other within the limits corresponding to the level of the noise in the image and to a user-defined tolerance preferences L for the noise-reduced image.

The largest averaging region R approximating the optimal one is found as follows.

Firstly, a selected pixel X is included into the region R. Then, the pairs of pixels $Y = X - v$, $Z = X + v$, where v is a shift vector, symmetrical with respect to point X and touching the already filled part of the region R, are considered pair by pair and a check is made whether the squared difference of their half sum $p(v) = (p(Y) + p(Z))/2$ from the average value of the pixels already included into R does not exceed the dispersion D of the noise present in the mentioned difference multiplied by some tolerance level L set by the user. If the pair of pixels passes the test, it is included into R. As long as the region R grows, the process continues with considering of pairs as described above. The process is stopped when no new pair of pixels passes the tests. Then the average pixel value over R is used as a value of pixel X in an image with reduced noise.

Better approximations of an optimal region R may be found in a similar way by inclusion of more tests for randomness of deviations of pixel values and tests for the presence near X

00716294400

of certain expected non-random details of the true image like thin lines. The found region R may be revised and made more dense and regular by inclusion into the region R of part of the internal points rejected in the first pass and by
5 smoothing the borderline of the region R.

The region R must be symmetric to eliminate the distortion of the image due to contribution of the gradient of true image intensity into the average value.

10 The limitation of deviations of half sums of pixel values from the average value over R limits the distortion of the noise-reduced image due to the contribution of the curvature of the true image intensity by about $\sqrt{DL}/4$.

15 Generally, the region R is elongated in the direction of minimal curvature of the image intensity. For pixels X near the boundary of smooth fragments, the region R becomes narrow and may be reduced to a line.

20 Due to statistical uncertainty of the boundary between the region R and surrounding image fragments, the averaging over the region R does some smearing of the image. However, the range of such smearing is several times smaller than the range of the smearing in the usual noise filtering methods, which is of the order of the filter diameter.

25 The choice of the averaging region R symmetric with respect to X is usual for all filters making the noise reduction, since it makes the average closer to the true value than in case of an asymmetric region. The present invention discloses that the region R is optimized individually for each point X and that in the selection of this region only the half sums $p(v)$ of pixel values at symmetrical points Y, Z are used
30 instead of individual pixel values. This makes the process of choice of region R insensitive to the gradient of intensity

of the true image. In particular, this property has the above-mentioned test written as the formula:

$$(p(v) - \text{Avr}_v(X))^2 < D(X, v)L,$$

where Avr_v here denotes the average over all pixel pairs earlier included into R and $D(X, v)$ stands for the dispersion of the difference $p(v) - \text{Avr}_v(X)$.

Dispersion $D(X, v) \sim D(X) \cdot (1/2 + 1/n)$, where n is a number of pixels in R , may be known from different sources: from analysis of earlier images obtained with the same technology, from the number of photons registered in case of Poisson statistics of noise, or from the image itself by means of the formula $D(X, v) = \text{Avr}((p - \text{Avr}(p))^2)$, where $p = p(v)$ and averaging is done over all pixel pairs earlier included in to R . The estimation of $D(X)$ and $D(X, v)$ may be done in many ways and is not an integral part of the invention.

The details of the algorithm picking up the pairs of pixels tested for possible inclusion into region R may be different and are not the integral part of the present invention. The process of checking is mentioned solely to give a general idea how the method may be realized. Actually, in a tested algorithm, the order, in which the pairs of pixels were tested, was fixed so as to allow the region R to grow continuously, by one-pixel layers of square shape until the deviation checks were positive. Every time when a new pair was added to the region R , the pixels touching to this pair were marked as possible extensions of R . The next picked pair of pixels was first checked for being marked. If it was unmarked, it was skipped without other more time-consuming tests. When none of the pixels in a next completed square layer passed the tests, the process of expansion of the region R stops.

The purpose of the additional checks for randomness of deviations is intended to clear the region R from compact groups of pixels (and their symmetrical partners) which pass the tests for individual pairs, but which deviate collectively too much to one side. If deviations are random, the squared deviation of the average of K half sums of pixel pairs from the true value $(P(X) - \text{Avr}_{kp}(v))^2$ may only exceed $2D(X)/K$ in a few percent of cases. If a group of pixel pairs deviates more, its exclusion from the region R will most probably make the average over the region R closer to the pixel value $P(X)$ of the true image. The check for the presence of certain suspected details is similar to the check above, but is more sensitive for deviation in groups of pixels of certain shapes.

The region R found in a one-pass process usually contains many holes, where most of the pixels do not deviate much, but at the time of their check during the first pass did not touch pixels already included into R. The revision of R with the account of points included afterwards and with slightly more liberal deviation test does not increase the size of R but makes it more solid.

The pixels in a borderline of a solid many-pixel region R should, normally, touch with 4 or 5 pixels belonging to this region. The rejection of peripheral points touching with less than 3 pixels belonging to the region R does not decrease significantly the number of pixels in the region R, but smoothes the borderline and decreases the risk of smearing distortions.

A second method of noise reduction using property (c) that the noise in the image is significantly correlated with the noise in other images will now be described.

The second method reduces noise at each point X of an image I_1 correlated with the noise at a corresponding point Y of an image I_2 with the variance-covariance matrix V for pixel values $p(X, I_1)$, $p(Y, I_2)$ by:

- 5 (1) obtaining from image I_2 a noise reduced image I_3 by any noise reduction method not using image I_1 ;

- (2) calculating the estimate $F(Y)$ given by the formula:

$$F(Y) = p(Y, I_2) - p(Y, I_3)$$

of the fluctuation of the pixel value at point Y;

- 10 (3) calculating the estimate $H(X, I_1)$ given by the formula:

$$H(X, I_1) = F(Y) \frac{V(p(X, I_1), p(Y, I_2))}{V(p(Y, I_2), p(Y, I_2))}$$

of fluctuation $G(X, I_1)$ of pixel value $p(X, I_1)$ in image I_1 ; and

- (4) obtaining from image I_1 a noise reduced image I_4 by subtracting from each pixel value of image I_1 the estimate of its fluctuation, which is given by the formula:

$$p(X, I_4) = p(X, I_1) - H(X, I_1).$$

If the matrix V as a function of X is known, implementation is straightforward and reduces to repeating calculations (2), (3), and (4) for all pixels X.

- 20 If the matrix V is not given, its estimate at each point X may be found by a standard method as average values over a small region around the point X and corresponding region around the point Y of products of deviations of pixel values from their average values over the same regions.

- 25 The second method reduces in image I_1 only the part of its noise which is correlated with the noise in image I_2 and does

not remove the part of noise in image I_1 which is independent from the noise in image I_2 . So the maximal coefficient of noise reduction by the second method is limited by the difference $1 - C^2$, where C is the correlation coefficient, which is given by the formula:

$$C = \frac{V(p(X, I_1), p(Y, I_2))}{\sqrt{V(p(X, I_1), p(X, I_1))V(p(Y, I_2), p(Y, I_2))}}.$$

If C^2 is close to 1.0, the noise reduction in image I_4 may be very deep. If C^2 is noticeably smaller than 1.0, image I_4 still contains noticeable independent noise. This noise may be reduced by applying to image I_4 other noise-reduction methods (including the first method).

The noise reduction by the second method has some specific consequence. It is related with the fact that image I_3 obtained from image I_2 contains smearing distortions. These distortions pass into estimates H and from them pass into the noise-reduced image I_4 , where they look as a kind of shadows of boundaries of objects on image I_2 .

Since images I_1 , I_2 are different, the boundaries of image fragments in image I_1 and image I_2 , generally do not coincide and shadows of boundaries of fragments of image I_2 do not smear details in image I_4 . These shadows obscure details in image I_4 much less than the original noise in image I_1 , so small details in image I_1 lost in the noise in image I_1 become visible after such noise reduction. By contrast, usual noise-reduction methods make small details less visible after noise reduction.

The intensity and widths of mentioned shadows of image I_2 in image I_4 depend on the choice of the method and parameters of noise reduction for image I_3 . The optimal choice of noise reduction for image I_2 depends on the structure of images I_1

and I_2 and of preferences of the user of image I_4 . The choice of the first method of the present invention for noise reduction in image I_2 is advantageous since it reduces the shadows of image I_2 obscuring the image I_4 .

- 5 The noise remaining in image I_4 can be further reduced by many methods. A comparison of image, obtained from image I_4 after noise reduction by the first method, with a true clean image shows that, when the noise correlation is present, the combination of the second and the first method makes very
10 deep noise reduction without noticeable distortions or smearing.

The roles of images I_1 and I_2 may be interchanged, so the noise may be reduced in image I_2 by the second method as well.

- 15 In an experiment with two artificially constructed images I_1 , I_2 , imitating images taken with high energy respective low energy X-rays, the noise was 95% correlated. To reduce noise in image I_2 , the first method was used with an additional check sensitive to the systematic deviation of local
20 intensity from the average one and reducing "shadows" of image I_2 in image I_4 .

- A comparison of image I_4 and noise-reduced image, obtained from image I_1 by the first method, gave the result that the first method is more efficient for large fragments (for
25 background), while the second method is advantageous for small fragments and details.

A third method of noise reduction using properties (a), (b), (c), and property (d) that images are reconstructed from common source images (data) will now be described.

- 30 The third method reduces noise in images I_1 and I_2 reconstructed (computed) as known smooth functions $I_1 =$

$a(S_1, S_2)$, $I_2 = b(S_1, S_2)$ from source images S_1 , S_2 with independent noise of known dispersion by combination of the first and the second method modified to exploit images S_1 , S_2 and functions a , b as follows:

5 (5) a noise reduced image I_3 is obtained from image I_2 by noise reduction by the first method, where the averaging region R is selected as the maximal region R around Y , which includes only the pairs of pixels symmetrically placed with respect to Y and; either

10 having the sums of values deviating from each other within the limits corresponding to the level of the noise in the image and to a tolerance preferences of the user of the noise-reduced image; or

corresponding to pairs of pixels in source images S_1 , S_2
 15 having the sums of values deviating from each other within the limits corresponding to the level of the noise in the images S_1 , S_2 and to a tolerance preferences of the user of the noise-reduced image;

(6) the estimate $F(Y)$ given by the formula:

20
$$F(Y) = p(Y, I_2) - p(Y, I_3)$$

of the fluctuation of the pixel value at point Y is calculated;

(7) the covariance matrix V for pixel values $p(X, I_1)$, $p(Y, I_2)$ at points X , Y on images I_1 , I_2 is computed in linear
 25 approximation as given by the formulae:

$$V(p(X, I_1), p(X, I_1)) = \left(\frac{\partial a}{\partial S_1} \right)^2 D_1 + \left(\frac{\partial a}{\partial S_2} \right)^2 D_2,$$

$$V(p(X, I_1), p(Y, I_2)) = \left(\frac{\partial a}{\partial S_1} \right) \left(\frac{\partial b}{\partial S_1} \right) D_1 + \left(\frac{\partial a}{\partial S_2} \right) \left(\frac{\partial b}{\partial S_2} \right) D_2,$$

$$V(p(Y, I_2), p(Y, I_2)) = \left(\frac{\partial b}{\partial S_1} \right)^2 D_1 + \left(\frac{\partial b}{\partial S_2} \right)^2 D_2,$$

where D_1 and D_2 are the noise dispersions in images S_1 , S_2 at points Z , T corresponding to point Y ;

- 5 (8) the estimate $H(X, I_1)$ given by the formula:

$$H(X, I_1) = F(Y) \frac{V(p(X, I_1), p(Y, I_2))}{V(p(Y, I_2), p(Y, I_2))}$$

of fluctuation $G(X, I_1)$ of pixel value $p(X, I_1)$ in image I_1 is calculated; and

- 10 (9) a noise reduced image I_4 is obtained from image I_1 by subtracting the estimate of fluctuation from each pixel value, wherein $P(X, I_4)$ is given by the formula:

$$p(X, I_4) = p(X, I_1) - H(X, I_1).$$

- 15 The relations $I_1 = a(S_1, S_2)$ and $I_2 = b(S_1, S_2)$ between images are pixel-wise, that is the point X on image I_1 corresponds uniquely to points Y , Z , T on images I_2 , S_1 , S_2 respectively. So, these relations can be written for pixels as given by the formulae:

$$p(X, I_1) = a(p(Z, S_1), p(T, S_2)),$$

$$p(Y, I_2) = b(p(Z, S_1), p(T, S_2)).$$

- 20 The implementation is straightforward and consists of performing operations (5)-(9) for all pixels of image I_1 . The simplest implementation of point (5) is to check only the difference between the sum of values and the double value of a central pixel (the check is done both for image I_1 and for

the source images S_1, S_2). The use of source images in the step (5) usually makes the quality of the region R found by the pixel-selection process described in the simplest implementation of the first method good enough without additional checks and boundary smoothing.

More advanced implementation of point (5) may check as well the deviation of the average source value from the average of the values of several pixel pairs touching the pixel pair in question. Such test locates more accurately the boundaries of the region R .

The most time-consuming step of the third method is the computation of the matrix V at all points. However, the ratio of its elements used in step (8) can be computed and tabulated beforehand as a two-argument function. In this case the computation of the matrix V is done quickly by interpolation and the whole noise reduction procedure takes about the same time as the calculation of image I_1 from images S_1, S_2 .

The smooth fragments of the source images correspond to smooth fragments on reconstructed images (but not vice versa, since reconstructed images contain smaller number of details than the source ones). Since the source images have relatively small noise, their use helps to define reliably the part of the region R , which does not contain details of the true image able to distort the average value, and helps to reduce statistical uncertainties of the boundaries. This makes the third method applicable in cases of very noisy (reconstructed) images, for which all other methods of noise reduction become inefficient.

In cases of less noisy images, when different noise reduction methods are applicable, the third method makes smearing distortions in image I_3 smaller, and image I_4 cleaner from

shadows of fragment boundaries in image I_2 . These shadows may become even indistinguishable.

The squared correlation coefficient for reconstructed images often exceeds 0.90 and noise dispersion can be reduced in
5 image I_4 more than a dozen times, if matrix V is known accurately enough. The knowledge of reconstruction functions a , b gives the possibility to compute V and the ratio between fluctuations H and F more accurately than by analysis of images I_1 , I_2 themselves and achieve the noise reduction
10 close to the theoretical limit.

In an experiment of the third method, an image I_1 and an image I_2 were reconstructed from two source images of simulated X-ray pictures of the combination of bone and tissue.

15 Reconstruction greatly amplifies the small intensity-dependent noise present in a source image (image S_1 or S_2), so the noise in images I_1 , I_2 was large and boundaries of fragments were smeared. This noise in I_1 was 95% correlated with the noise in I_2 . In this case, difficult to the first
20 method, the third method remained efficient and gave an image where the "shadows" of other image are noticeable, but the noise reduction is deep and small details are reproduced without any smearing.

Preferably, the methods of the present invention is performed
25 by software code, located in the internal memory of a computer, and executed by a processor of that computer.

It will be obvious that the present invention may be varied in a plurality of ways. Such variations are not to be regarded as departure from the scope of the present
30 invention. All such variations as would be obvious to one

	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

CLAIMS

1. A method for reduction of noise in an image including a plurality of pixels, comprising averaging pixel values over a region (R), characterized by the steps of:

- 5 - adding a selected pixel to the region (R);
- grouping pixels adjacent the region (R) in pairs, wherein the pixels of each pair being oppositely located with respect to said selected pixel;
- adding said pairs, pair by pair, to the region (R) in
10 dependence on that the squared difference of the selected pixel value from the pairs half sums does not exceed the dispersion (D) of the noise of said difference multiplied by a tolerance level (L);
- repeating said step of grouping and said step of adding
15 said pairs until that, in said step of adding said pairs, the condition for adding said pairs is not fulfilled for any pair;
- averaging the pixel values of said region (R); and
- using the thus averaged pixel value for said selected pixel
20 in reconstruction of said image.

2. The method as claimed in claim 1, wherein said step of grouping excludes grouping of pixels previously being grouped in pairs.

3. The method as claimed in claim 1, wherein said step of
25 adding said pairs excludes pairs that do not touch any of the pairs already included in said region (R).

4. The method as claimed in claim 1, 2 or 3, wherein said method is performed a second time and wherein said step of

grouping during said second time only includes pixels rejected during the first performance of said method.

5 The method as claimed in any of claims 1-4, wherein said step of adding said pairs is performed in dependence on that the squared difference of an average of pixel values in the region (R) from the pairs half sum does not exceed the dispersion (D) of said difference multiplied by a tolerance level (L).

10 6. A method for reduction of noise in an image including a plurality of pixels, characterized by the steps of:

- obtaining a noise reduced value of a first pixel;
- calculating an estimate of the fluctuation of said noise reduced value of said first pixel;
- calculating an estimate of the fluctuation at a second pixel, wherein said fluctuation of said second pixel is correlated to said fluctuation of said first pixel; and
- obtaining a noise reduced value of said second pixel by subtracting said fluctuation at said second pixel.

20 7. The method as claimed in claim 6, wherein the absolute value of said correlation is at least 0.8, preferably 0.9, and more preferably 0.95.

8. The method as claimed in claim 6 or 7, wherein said first and said second pixels are located in different images.

25 9. A method for reduction of noise in an image including a plurality of pixels, comprising averaging pixel values over a first region (R) around a selected pixel (X), characterized by the steps of:

- finding a second pixel (X1) corresponding to said selected pixel (X);

- adding said second pixel (X1) to a second region (R1);

- grouping pixels adjacent the second region (R1) in pairs,
5 wherein the pixels of each pair being oppositely located with respect to said selected pixel;

- adding said pairs, pair by pair, to the second region (R1) in dependence on that the squared difference of the selected pixel value from the pairs half sums does not exceed the
10 dispersion (D) of the noise of said difference multiplied by a tolerance level (L);

- repeating said step of grouping and said step of adding said pairs until that, in said step of adding said pairs, the condition for adding said pairs are not fulfilled for any
15 pair;

- averaging the pixel values of the first region (R), which corresponds to the second region (R1); and

- using the thus averaged pixel value for the selected pixel (X) of said first region (R) in reconstruction of said image.

20 10. The method as claimed in claim 9, wherein said step of grouping excludes pixels previously grouped in pairs.

11. The method as claimed in claim 9 or 10, wherein said dispersion (D) is based on the region (R1) instead of said selected pixel.

25 12. The method as claimed in any of claims 9-11, wherein said step of adding said pairs is performed in dependence on that the squared difference of an average of pixel values in the region (R1) from the pairs half sum does not exceed the

dispersion (D) of said difference multiplied by a tolerance level (L).

13. The method as claimed in any of claims 9-12, wherein said second region (R1) is located in an image, which is different
5 than the image wherein said first region (R) is located.

14. The method as claimed in any of claims 9-13, wherein said noise reduced image is further noise reduced by the method according to any of claims 6-8.

15. The method as claimed in any of claims 9-14, wherein said noise reduced image is further noise reduced by the method
10 according to any of claims 1-5.

16. A computer program product directly loadable into the internal memory of a computer, said computer program product comprising software code portions for performing the method
15 as claimed in any of claims 1-15 when said computer program product is run on said computer.

ABSTRACT

09716293-112400
The present invention relates to a method for reduction of noise in an image including a plurality of pixels, comprising averaging pixel values over a region (R), comprising the steps of: adding a selected pixel to the region (R); grouping pixels adjacent the region (R) in pairs, wherein the pixels of each pair being oppositely located with respect to said selected pixel; adding said pairs, pair by pair, to the region (R) in dependence on the squared difference of the selected pixel value from the pairs half sums does not exceed the dispersion (D) of the noise of said difference multiplied by a tolerance level (L); repeating said step of grouping and said step of adding said pairs until that, in said step of adding said pairs, the condition for adding said pairs is not fulfilled for any pair; averaging the pixel values of said region (R); and using the thus averaged pixel value for the selected pixel of said region (R) in reconstruction of said image.

BIRCH, STEWART, KOLASCH & BIRCH, LLP

P.O. Box 747 • Falls Church, Virginia 22040-0747
 Telephone: (703) 205-8000 • Facsimile: (703) 205-8050

PLEASE NOTE:
 YOU MUST
 COMPLETE THE
 FOLLOWING

COMBINED DECLARATION AND POWER OF ATTORNEY FOR PATENT AND DESIGN APPLICATIONS

As a below named inventor, I hereby declare that: my residence, post office address and citizenship are as stated next to my name; that I verily believe that I am the original, first and sole inventor (if only one inventor is named below) or an original, first and joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

NOISE REDUCTION IN IMAGES

Insert Title:

Fill in Appropriate
 Information -
 For Use Without
 Specification
 Attached:

the specification of which is attached hereto. If not attached hereto,

the specification was filed on _____ as
 United States Application Number _____;
 and amended on _____ (if applicable) and/or
 the specification was filed on _____ as PCT
 International Application Number _____; and was
 amended under PCT Article 19 on _____ (if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56.

I do not know and do not believe the same was ever known or used in the United States of America before my or our invention thereof, or patented or described in any printed publication in any country before my or our invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representative or assigns more than twelve months (six months for designs) prior to this application, and that no application for patent or inventor's certificate on this invention has been filed in any country foreign to the United States of America prior to this application by me or my legal representatives or assigns, except as follows.

I hereby claim foreign priority benefits under Title 35, United States Code, §119(a)-(d) of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Priority Claimed

<u>0003608-7</u> (Number)	<u>Sweden</u> (Country)	<u>October 6, 2000</u> (Month/Day/Year Filed)	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
_____ (Number)	_____ (Country)	_____ (Month/Day/Year Filed)	<input type="checkbox"/> Yes	<input type="checkbox"/> No
_____ (Number)	_____ (Country)	_____ (Month/Day/Year Filed)	<input type="checkbox"/> Yes	<input type="checkbox"/> No
_____ (Number)	_____ (Country)	_____ (Month/Day/Year Filed)	<input type="checkbox"/> Yes	<input type="checkbox"/> No

I hereby claim the benefit under Title 35, United States Code, §119(e) of any United States provisional applications(s) listed below.

Insert Provisional
 Application(s):
 (if any)

_____ (Application Number)	_____ (Filing Date)
_____ (Application Number)	_____ (Filing Date)

All Foreign Applications, if any, for any Patent or Inventor's Certificate Filed More than 12 Months (6 Months for Designs) Prior to the Filing Date of This Application:

Country	Application Number	Date of Filing (Month/Day/Year)
_____	_____	_____
_____	_____	_____

Insert Requested
 Information:
 (if appropriate)

I hereby claim the benefit under Title 35, United States Code, §120 of any United States and/or PCT application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States and/or PCT application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information which is material to the patentability as defined in Title 37, Code of Federal Regulations, §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

Insert Prior U.S.
 Application(s):
 (if any)

_____ (Application Number)	_____ (Filing Date)	_____ (Status - patented, pending, abandoned)
_____ (Application Number)	_____ (Filing Date)	_____ (Status - patented, pending, abandoned)

Attorney Docket No.

I hereby appoint the following attorneys to prosecute this application and/or an international application based on this application and to transact all business in the Patent and Trademark Office connected therewith and in connection with the resulting patent based on instructions received from the entity who first sent the application papers to the attorneys identified below, unless the inventor(s) or assignee provides said attorneys with a written notice to the contrary:

Raymond C. Stewart	(Reg. No. 21,066)	Terrell C. Birch	(Reg. No. 19,382)
Joseph A. Kolasch	(Reg. No. 22,463)	James M. Slattery	(Reg. No. 28,380)
Bernard L. Sweeney	(Reg. No. 24,448)	Michael K. Mutter	(Reg. No. 29,680)
Charles Gorenstein	(Reg. No. 29,271)	Gerald M. Murphy, Jr.	(Reg. No. 28,977)
Leonard R. Svensson	(Reg. No. 30,330)	Terry L. Clark	(Reg. No. 32,644)
Andrew D. Meikle	(Reg. No. 32,868)	Marc S. Weiner	(Reg. No. 32,181)
Joe McKinney Muncy	(Reg. No. 32,334)	Donald J. Daley	(Reg. No. 34,313)
John W. Bailey	(Reg. No. 32,881)	John A. Castellano	(Reg. No. 35,094)
Gary D. Yacura	(Reg. No. 35,416)		

Send Correspondence to:

BIRCH, STEWART, KOLASCH & BIRCH, LLP

or **Customer No. 2292**

P.O. Box 747 • Falls Church, Virginia 22040-0747

Telephone: (703) 205-8000 • Facsimile: (703) 205-8050

PLEASE NOTE:
YOU MUST
COMPLETE
THE
FOLLOWING:

↓

Full Name of First
or Sole Inventor:
Insert Name of
Inventor
Insert Date This
Document is Signed

Insert Residence
Insert Citizenship

Insert Post Office
Address

Full Name of Second
Inventor, if any:
see above

Full Name of Third
Inventor, if any:
see above

Full Name of Fourth
Inventor, if any:
see above

Full Name of Fifth
Inventor, if any:
see above

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

GIVEN NAME/FAMILY NAME Skiff Sokolov		INVENTOR'S SIGNATURE <i>Skiff Sokolov</i>	DATE* 2000. 10. 12
Residence (City, State & Country) Lidingö, Sweden		CITIZENSHIP Russian	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country) Kostervägen 5, SE-181 35 Lidingö, Sweden			
GIVEN NAME/FAMILY NAME		INVENTOR'S SIGNATURE	DATE*
Residence (City, State & Country)		CITIZENSHIP	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)			
GIVEN NAME/FAMILY NAME		INVENTOR'S SIGNATURE	DATE*
Residence (City, State & Country)		CITIZENSHIP	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)			
GIVEN NAME/FAMILY NAME		INVENTOR'S SIGNATURE	DATE*
Residence (City, State & Country)		CITIZENSHIP	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)			
GIVEN NAME/FAMILY NAME		INVENTOR'S SIGNATURE	DATE*
Residence (City, State & Country)		CITIZENSHIP	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)			
GIVEN NAME/FAMILY NAME		INVENTOR'S SIGNATURE	DATE*
Residence (City, State & Country)		CITIZENSHIP	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)			

*DATE OF SIGNATURE